

# DISC CENTER® Rundbürsten

für Winkelschleifer und stationäre Maschinen

Abmessung			Bohrung		Gewinde G	Orig. OSBORN Stahldraht				Orig. rostfreier OSBORN St. 0,40 Best.-Nr.	Adapter	max. min <sup>-1</sup>	Stand. Verp.
D mm	A mm	T mm	B mm	Zoll		0,30 Best.-Nr.	0,35 Best.-Nr.	0,50 Best.-Nr.	0,63 Best.-Nr.				
<b>Ø 150</b>													
150	6	38	22,2	7/8"	---	---	---	<b>9906-026 501</b>	---	---	F	12.000	12
150	25	38	22,2	7/8"	---	<b>9906-026 246</b>	<b>9906-026 247</b>	---	---	<b>9906-026 629</b>	F	12.000	12
150	13	38	22,2	7/8"	---	---	---	---	<b>9906-026 249</b>	---	F	12.000	12
150	6	38	---	---	M14x2	---	---	<b>9906-026 500</b>	---	---	---	12.000	10
150	6	38	---	---	5/8"NC	---	---	9906-026 045	---	---	---	12.000	10
150	25	38	---	---	5/8"NC	---	---	---	<b>9906-026 047</b>	---	---	12.000	10
<b>Ø 165</b>													
165	6	32	22,2	7/8"	---	---	---	<b>9886-026 051</b>	---	---	F	12.000	12
165	10	32	22,2	7/8"	---	---	---	---	<b>9886-026 039</b>	---	F	12.000	12
165	6	32	---	---	5/8"NC	---	---	9906-026 048	---	---	---	12.000	10
165	10	32	---	---	5/8"NC	---	---	---	<b>9906-026 039</b>	---	---	12.000	2
<b>Ø 171</b>													
171	6	29	22,2	7/8"	---	---	---	<b>9706-026 904</b>	---	---	F	12.000	12
171	6	29	---	---	5/8"NC	---	---	<b>9906-026 904</b>	---	---	---	12.000	10
<b>Ø 178</b>													
178	6	38	22,2	7/8"	---	---	---	<b>9906-026 051</b>	---	---	F	12.000	12
178	13	44	22,2	7/8"	---	---	---	---	<b>9906-026 551</b>	---	F	12.000	12
178	6	38	---	---	M14x2	---	---	9906-026 053	---	---	---	12.000	10
178	6	38	---	---	5/8"NC	---	---	9906-026 052	---	---	---	12.000	10
178	13	44	---	---	M14x2	---	---	---	9906-026 552	---	---	12.000	10
178	13	44	---	---	5/8"NC	---	---	---	9906-026 553	---	---	12.000	10

Andere Abmessungen und Drahtstärken auf Anfrage! Die lagermäßig geführten Artikel sind **besonders hervorgehoben!**