

DISC CENTER® Rundbürsten

für stationäre Maschinen

Abmessung			Bohrung		Gewinde G	Orig. OSBORN Stahldraht				Adapter	max. min ⁻¹	Stand. Verp.	
D mm	A mm	T mm	B mm	Zoll		0,30 Best.-Nr.	0,35 Best.-Nr.	0,50 Best.-Nr.	0,63 Best.-Nr.				
Ø 200 besonders aggressiv													
200	16	32	50,8	2"	---	9907-026 099	---	---	---		1A	8.000	6
Ø 200													
200	18	46	32	1 1/4"	---	---	9906-026 127	9906-026 245	9906-026 133		3A	8.000	12
Ø 250 besonders aggressiv													
250	18	48	50,8	2"	---	---	9906-026 198	---	---		4M	4.500	6
Ø 250													
250	18	43	50,8	2"	---	9906-026 182	9906-026 183	9906-026 185	---		4M	4.500	6
Ø 300													
300	16	57	50,8	2"	---	---	9906-026 276	9906-026 279	1306-026 279		4M	3.600	2
300	18	57	50,8	2"	---	9906-026 171	9906-026 172	9906-026 236	---		4M	3.600	2
Ø 380													
380	20	67	50,8	2"	---	---	9906-026 166	9906-026 167	---		4M	3.600	2

Andere Abmessungen und Drahtstärken auf Anfrage! Die lagermäßig geführten Artikel sind **besonders hervorgehoben!**